


Rundstahl, blank



- 17 -

gezogen nach DIN 671 (ISO h9)

DIN EN 10278

gezogen poliert oder geschliffen poliert nach DIN 670 (ISO h8) / DIN 59361 (ISO h6)

Stablänge ca. 3,0-3,2 m

Abnahmeprüfzeugnis EN 10204/3.1

Abmessung	kg/mtr.	W.-Nr. 1.4021	W.-Nr. 1.4112	W.-Nr. 1.4122	W.-Nr. 1.4104	W.-Nr. 1.4301	W.-Nr. 1.4305	W.-Nr. 1.4404	W.-Nr. 1.4435	W.-Nr. 1.4542
2,0	0,025					x	x			
2,5	0,039				x	x				
3,0	0,056				x	x	x	x	x	
3,5	0,076					x	x			
4,0	0,099				x	x	x	x	x	
4,5	0,125				x	x	x			
5,0	0,154	x	x		x / h8	x	x	x	x	
6,0	0,222	x	x / h8		x / h8	x ¹ / h6	x / h8	x	x	
7,0	0,302	x	x		x / h8	x	x / h8	x	x	
8,0	0,392	x	x		x / h8	x ¹ / h6	x / h8	x	x	
9,0	0,499	x				x	x			
10,0	0,617	x	x		x	x ¹ / h6	x / h8	x / h6	x	
11,0	0,746	x			x	x	x			
12,0	0,888	x	x		x	x ¹	x / h8	x / h6	x	
13,0	1,042	x	x		x	x	x	x		
14,0	1,208	x	x	x	x	x ¹	x	x		
14,1	1,230				x					
15,0	1,387	x	x		x	x ¹ / h6	x	x / h6	x	
15,1	1,410				x					
16,0	1,578	x		x	x / h8	x ¹	x	x / h6	x	
16,1	1,600				x					
17,0	1,782				x	x	x			
18,0	1,998	x			x	x ¹	x	x	x	
20,0	2,446	x	x		x / h8	x ¹ / h6	x	x / g6	x / h8	
22,0	2,984	x			x	x / h6	x	x		
23,0	3,262				x	x	x			
24,0	3,551				x	x	x	x		
25,0	3,853	x	x	x	x	x ¹ / h6	x ²	x / g6	x	
26,0	4,168				x		x	x	x	
27,0	4,495					x	x			
28,0	4,834				x	x	x	x		
30,0	5,549	x	x	x	x	x ¹ / h6	x ²	x / g6	x	
31,0	5,920					x				

¹⁾ Auch in Stablänge 6,0 m vorrätig!

²⁾ Auch mit Toleranzfeld f 8 vorrätig, Stablänge ca. 4,0 m!


Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar!

☎ 07042-8261-0 📠 07042-8261-11 ✉ info@e-h-p.de 🌐 www.e-h-p.de



Rundstahl, blank

- 18 -



gezogen nach DIN 671 (ISO h9)

DIN EN 10278

gezogen poliert oder geschliffen poliert nach DIN 670 (ISO h8) / DIN 59361 (ISO h6)

Stablänge ca. 3,0-3,2 m

Abnahmeprüfzeugnis EN 10204/3.1

Abmessung	kg/mtr.	W.-Nr. 1.4021	W.-Nr. 1.4112	W.-Nr. 1.4122	W.-Nr. 1.4104	W.-Nr. 1.4301	W.-Nr. 1.4305	W.-Nr. 1.4404	W.-Nr. 1.4435	W.-Nr. 1.4542
32,0	6,313	x				x	x	x	x	
34,0	7,127				x	x	x			
35,0	7,553	x	x	x	x	x ¹⁾ / h6	x	x / h6	x	
36,0	7,990					x	x			
38,0	8,903				x	x	x	x		
40,0	9,865	x	x	x	x	x ¹⁾ / h6	x ²⁾	x ¹⁾ / h6	x	
42,0	10,880				x	x	x	x		
45,0	12,480	x	x	x	x	x	x	x	x	
50,0	15,410	x	x	x	x	x ¹⁾ / h6	x	x ¹⁾ / h6	x	
55,0	18,650	x			x	x	x	x	x	
58,0	20,730							x		
60,0	22,200	x			x	x ¹⁾	x	x ¹⁾ / h6	x	
65,0	26,050	x			x	x	x	x	x	
70,0	30,210	x			x	x ¹⁾	x	x ¹⁾	x	
75,0	34,680					x	x	x		
80,0	39,460					x	x	x	x / h8	
85,0	44,500					x				
90,0	49,940							x ¹⁾		
100,0	61,650							x		

¹⁾ Auch in Stablänge 6,0 m vorrätig!

²⁾ Auch mit Toleranzfeld f 8 vorrätig, Stablänge ca. 4,0 m!

Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar!

Notizen

